

# MATERIAL SAFETY DATA SHEET

MSDS Name: Furniture Lacquer Gloss  
MSDS Number: 346000  
MSDS Date: 9/18/2002



## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME AND CODE** Furniture Lacquer 346000  
**COMPANY NAME AND ADDRESS** Heinrich König & Co.  
An der Rosenhelle 5  
D-61138 Niederdorfelden  
Germany  
**EMERGENCY CONTACT** 49 / 6101 / 53 60 50 (R & D)  
**TELEPHONE/FAX** 49 / 6101 / 53 60 - 0 (General)  
49 / 6101 / 53 60 11 (Fax)  
**DATE PREPARED** 03/14/02

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS NUMBER	WT. %	OSHA		ACGIH		UNITS
			TWA	STEL	TWA	STEL	
Toluene	108-88-3	2.1	100	150	50	N/E	ppm
n-Butyl Alcohol	71-36-3	1.9	N/E	CL 50	N/E	CL 50	ppm
Ethyl Acetate	141-78-6	10.0	400	N/E	400	N/E	ppm
1-methoxy-2-propanol	107-98-2	4.9	100	150	100	150	ppm
Methyl Isobutyl Ketone	108-10-1	8.7	50	75	50	75	ppm
Acetone	67-64-1	6.3	750	1000	500	750	ppm
n-Butyl Acetate	123-86-4	11.0	150	200	150	200	ppm
Isopropyl Alcohol	67-63-0	2.7	400	500	400	500	ppm
Dimethylether	115-10-6	45.0	N/E	N/E	N/E	N/E	ppm
Dibutyl Phthalate	84-74-2	1.4	5	N/E	5	N/E	mg/m3
Dipropylene Glycol Methyl Ether	34590-94-8	1.0	100	150	100	150	ppm

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER!**  
FLAMMABLE LIQUID AND VAPOR  
VAPOR MAY CAUSE FLASH FIRE  
VAPOR HARMFUL  
CAUSES EYE AND SKIN IRRITATION  
HARMFUL OR FATAL IF SWALLOWED

### POTENTIAL HEALTH EFFECTS

#### INHALATION

Harmful if inhaled. High vapor concentrations may cause drowsiness or unconsciousness. May cause headaches and dizziness.

#### EYE CONTACT

Causes eye irritation.

#### SKIN

May cause skin irritation. May be harmful if absorbed through the skin.

#### INGESTION

Harmful or fatal if swallowed. Pulmonary aspiration hazard. Product may enter lungs and cause damage.

#### CHRONIC

Prolonged or repeated overexposure may cause liver and kidney damage. The following components are listed by OSHA, IARC or NTP as a potential carcinogen: None

# MATERIAL SAFETY DATA SHEET

MSDS Name: Furniture Lacquer Gloss  
MSDS Number: 346000  
MSDS Date: 9/18/2002



## 4. FIRST AID MEASURES

<b>INHALATION</b>	Remove to fresh air. Keep patient calm and warm. If not breathing, give mouth-to-mouth resuscitation. If unconscious, place in recovery position and seek medical attention.
<b>EYE CONTACT</b>	Flush continuously with fresh water for at least 15 minutes, holding the eyelids apart. Seek medical attention.
<b>SKIN</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water. Do NOT use solvents or thinner. Remove contaminated clothing or shoes. Obtain medical attention if irritation persists.
<b>INGESTION</b>	If accidentally swallowed, obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. If possible, do not leave individual unattended.

## 5. FIRE FIGHTING MEASURES

<b>FLASH POINT</b>	-4 C°
<b>METHOD USED</b>	CC
<b>LOWER EXPLOSION LIMIT</b>	2.4 Vol. %
<b>UPPER EXPLOSION LIMIT</b>	18.6 Vol. %
<b>EXTINGUISHING MEDIA</b>	Use alcohol-resistant foam, carbon dioxide (CO <sub>2</sub> ) or dry powder fire extinguisher.
<b>UNSUITABLE MEDIA</b>	Water spray may not be effective.
<b>FIRE-FIGHTING EQUIPMENT</b>	Wear full fire-fighting bunker gear and respiratory protection (SCBA).
<b>DANGER IN CASE OF ACCIDENT</b>	Fire will produce dense black smoke. Exposure to decomposition-products may cause danger to health. Wear appropriate equipment. Cool closed containers exposed to fire with water. If possible, remove from dangerous area. Do NOT allow runoff from water (caused from fire-fighting) to enter drains or water streams.

## 6. ACCIDENTAL RELEASE MEASURES

<b>PERSONAL PRECAUTIONS</b>	Immediately contact emergency personnel. Eliminate all sources of ignition. Use suitable protective equipment (Section 8). Use explosion-proof equipment. The very fine particles can cause fire or explosion.
<b>CLEAN-UP MEASURES</b>	If emergency personnel are unavailable, contain spilled liquid with non-combustible absorbent materials e.g. sand, earth, and vermiculite. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Obey all local, state and federal laws regarding chemical spills. Do NOT allow entering drains or water streams.

# MATERIAL SAFETY DATA SHEET

MSDS Name: Furniture Lacquer Gloss  
MSDS Number: 346000  
MSDS Date: 9/18/2002



## 7. HANDLING AND STORAGE

### HANDLING

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits.

Additionally, the product should only be used in areas from which all exposed lights and other sources of ignition have been excluded. Electrical equipment should represent the appropriate safety-standard.

Preparation may charge electro-statically: always use ground-wires when transferring from one container to another. Operators should wear antistatic footwear and clothing. The floors should be in connection with electrical ground. Only use spark-free tools.

Avoid skin and eye contact. Avoid inhalation of vapor and spray-mist. Smoking, eating and drinking should be prohibited in application-area.

### STORAGE

Keep container tightly closed. Store between 15 and 30 °C in a dry and well-ventilated area away from heat, sparks and direct sunlight. Keep away from oxidizing agents, from strongly alkaline and strongly acidic materials. Empty containers may retain hazardous properties. Do not cut, puncture or weld on or near the container. Store large quantities only in buildings designed to comply with OSHA 1910.106.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### ENGINEERING CONTROLS

Use exhaust ventilation to keep airborne concentrations below exposure limits

### PERSONAL PROTECTIVE EQUIPMENT

#### EYES

Chemical splash goggles in compliance with OSHA are advised.

#### SKIN

Wear resistant gloves such as Buna-N (nitrile rubber). Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

#### RESPIRATORY

When respiratory protection is required, or concentrations are unknown use a NIOSH/MSHA approved air-purifying respirator equipped with organic vapor cartridges or canisters. For emergency and other conditions where exposure limit may be greatly exceeded, use an approved positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply.

### EXPOSURE GUIDLINES

See Section 2 for ingredient exposure limits.

# MATERIAL SAFETY DATA SHEET

MSDS Name: Furniture Lacquer Gloss

MSDS Number: 346000

MSDS Date: 9/18/2002



## 9. PHYSICAL AND CHEMICAL PROPERTIES

	TYPICAL VALUE	UNITS
PHYSICAL STATE	Aerosols	
COLOR	Typical	
ODOR	Typical	
pH	Not Available	
VAPOR PRESSURE	3600	mbar
VAPOR DENSITY	Heavier than air	
BOILING POINT	25	°C
MELTING POINT	Not Available	°C
SOLUBILITY IN WATER	Not Soluble	
SPECIFIC GRAVITY	0.77	g/cm <sup>3</sup>
PERCENTAGE OF VOC	94	%
SOLIDS WEIGHT CONTENT	6.36	%
SOLIDS VOLUME CONTENT	5.76	liters/100kg
WATER CONTENT	0	%

## 10. STABILITY AND REACTIVITY

**STABILITY** Stable under recommended storage and handling conditions.

**CONDITIONS TO AVOID** Avoid static discharge. Avoid heat, sparks and open flame.

**INCOMPATIBILITY** Keep away from strong oxidizers, alkaline and acidic materials.

**HAZARDOUS DECOMPOSITION PRODUCTS** Combustion may produce carbon monoxide, carbon dioxide, oxides of nitrogen, smoke and other asphyxiants.

**HAZARDOUS POLYMERIZATION** Will not polymerize.

## 11. TOXICOLOGICAL INFORMATION

There are no data available on the preparation itself. Exposure to component solvents vapors concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nerve-system.

Symptoms and signs include headache; dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

## 12. ECOLOGICAL INFORMATION

There are no data available on the preparation itself.  
The product should not be allowed to enter drains or watercourses.

## 13. DISPOSAL CONSIDERATIONS

Do not allow the product to enter drains or watercourses. Empty containers should not be used for other purposes and are to be handled as industrial waste according to local, state and federal regulations.

# MATERIAL SAFETY DATA SHEET

MSDS Name: Furniture Lacquer Gloss  
MSDS Number: 346000  
MSDS Date: 9/18/2002



## 14. TRANSPORT INFORMATION

**SHIPPING NAME** AEROSOLS, FLAMMABLE, UN1950  
**HAZARD CLASS** 2.1  
**PACKING GROUP** II  
**UN NUMBER** UN1950

## 15. REGULATORY INFORMATION

**TSCA** Components of this product are listed on the Toxic Substance Control Act inventory.  
**OSHA** Hazardous by definition of Hazardous Communication Standard (29 CFR 1910.1200).

REPORTABLE INGREDIENTS	CAS NUMBER	WT%	SARA TITLE III (313)	Proposition 65 (CALIFORNIA)
Toluene	108-88-3	2.1	Y	Y
n-Butyl Alcohol	71-36-3	1.9	Y	N
Methyl Isobutyl Ketone	108-10-1	8.7	Y	N
Dibutyl Phthalate	84-74-2	1.4	Y	N

## 16. OTHER INFORMATION

The information in this MSDS is meant as a description of the safety requirements for our product; it is not to be considered a guarantee of the products' properties.

To the best of our knowledge, the information contained herein is accurate. However, neither Coating Development Group, Inc. nor Heinrich König and Company assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exists.